30+ Years of Focus on Food Machinery. All to Create Industry-Leading Noodle Production Equipment. 30余年专注食品机械,只为打造行业领先的面条生产设备。





Add: No.2 Industrial Avenue, Guandu Industrial Zone, Zhanjiang, Guangdong, 524051 China.

地址: 广东省湛江市官渡工业园工业大道2号 邮政编码: 524051

Tel/电话: +86-759-3837628 3837627 Web/网址: www.heshan-machines.com Email/邮箱: marketing@heshan.com





OFFICIAL WEBSITE

中文官方网站





Wheat Flour Noodles Production Line 小麦粉类面条生产线

Heshan Noodle Production Lines: Automated, Intelligent, and Efficient, Providing Reliable and Stable Production Assurance for Global Food Manufacturers. 河山面条生产线: 自动化、智能化、高效化,为全球食品制造商提供可靠、稳定的生产保障。



www.heshan-machines.com

Contents

About Us

关于我们

Process Flow 工艺流程

03









Fried Bag Instant Noodle Production Line 油炸袋装方便面生产线



Dried Noodle Production Line 烘干面产线



Yee Mee Crispy Fried Instant Noodle Production Line 伊面生产线



Fried Cup / Bowl Instant Noodle Line 油炸杯(碗)装方便面生产线



Stick Noodle Production Line 挂面生产线



Wonton Skin & Fresh Noodle Production Line 云吞皮和新鲜面条生产线

About Us 关于我们

30+ Years Innovating
Excellence –
Pioneering Intelligent
Solutions for Food Industry

三十余载深耕,智造食品机械行业标杆



Establishment In 成立于 1998

Covered Area 占地面积 **286,000.00**sq. ff 平方英尺

Invested Up To 累计投资

 $\mathfrak{S}3,500,000.00$

HESHAN MACHINERY CO., LTD. is a leading manufacturer specializing in R&D and production of food processing machinery. Since its founding in 1998, innovation has been the driving force behind our advancements in automated noodle production technology. In collaboration with Siemens, we pioneered the development of fully automated control systems for: Rice vermicelli, Fresh rice noodles (Ho Fun), Yee Mee (E-Fu noodles) and Instant noodles. Our cutting-edge solutions have set new industry standards, ushering in a new era of intelligent food production.

Heshan continues to grow stronger as its high-tech and competitive products penetrate deeper into the market. Since 2004, Heshan (Zhanjiang) has cumulatively invested US\$8,500,000.00, making the new plant area even more eye-catching. Within the 286,000.00 square-foot new plant area, there stand three modern production workshops of 128,000.00 square feet in total, as well as a 9,850.00 square-foot office building with a contemporary design.

We not only provide all kinds of high quality food machinery under the supervision and management of ISO 2000, but also provides thoughtful and considerate services including pre-sales, ongoing-sales service and after-sales services. We've gained our reputation with more and more appreciation from customers, and we've been looking forward to sharing more joy with our customers.


河山机器有限公司是专业从事食品机械的研究和制造企业,自 1998 年成立之日起,创新的信念就伴随着米面制品自动化生产行业不断发展,河山率先与西门子合作,开发米粉、河粉、伊面、方便面等生产线自动化控制系统,从而将该行业技术引领到新纪元。

河山随着具有高科技和富有竞争力的产品深入市场而不断壮大,2004年起至今河山(湛江)累计投资 US\$8,500,000.00,让新厂区更加引人注目,286,000.00平方英尺的全新厂区内屹立着三幢128,000.00平方英尺的现代化生产车间和9.850.00平方英尺的富有时代感办公楼。

河山 160 名高素质员工严格施行 ISO2000 的管理模式,不仅为全球客户提供高质量的各类食品机械设备,更能热诚为每位客商提供尽善尽美的销前,销中和销后全方位的优质服务。河山因为有众多客户的赏识而出类拔萃,河山也时刻期待着与客户分享更多的喜悦。








Fried Bag Instant Noodle Production Line

油炸袋装方便面生产线





>

Features 特点

Automated control system of Heshan Instant Noodle Production Line integrates Siemens' industrial software with premium European/Japanese components. Utilizing PLC synchronization technology, the production line achieves full automation with three core features: Real-time process tracking, Photoelectric monitoring, Multi-axis motion control;

This configuration ensures 98% operational efficiency while reducing labor costs by 70%, requiring only 3 operators for full production control.

河山油炸袋装方便面生产线自动控制系统融合西门子工业软件与欧洲 / 日本优质部件,通过 PLC 同步技术实现全自动化生产,核心功能包括:实时流程追踪、光电监测系统、多轴协同控制;


该系统运行效率达 98%,人力成本降低 70%,仅需 3 名操作员即可完成全线管控。

Specification 规格	FBN-200A	FBN-200B	FBN-300A	FBN-300B	FBN-400A	FBN-400B	FBN-500A	FBN-500B	FBN-600A	FBN-600B	FBN-700	FBN-800	FBN-900	FBN-1000	FBN-1200	FBN-1500
Output (bags/8h) 产量 (袋/8h)(70g/bag)	40,000 60,000 70,000 90,000 100,000 120,000 130,000 150,000 160,000 180,000 200,000 230,000 260,000 290,000 350,000 440,000															
Rated power 额定功率(kW)	50-160															
Steam consumption 蒸汽消耗量(kg/h)	900-4500															
Operator/shift 操作员/班次	5-10															
Overall Dimensions 外形尺寸(L*W*H)(M)		(80-120)*(3-5)*6.5														

生产设备

07/08







Alkaline Liquid Tank 苏打水桶



Alkaline Liquid Measuring Tank 苏打水计量桶





Flour Mixing Machine 和面机

◆ Feeding Machine & Compound Rolling Machine 喂料机 & 复合压片机



Continuous Rolling Machine 连续压片机









Wave Forming Machine 波纹成型

○ Cutting Machine 切断机



◆ Three-Layer Steaming Machine 三层蒸面机




Automatic Frying Machine 油炸机



▲ External Pipeline Of Noodle Steaming Machine 蒸面机外管道

生产设备









Oil Filter 过滤机




Occiling Machine 冷却机



河山机器有限公司 HESHAN MACHINERY CO.,LTD.

Fried Cup / Bowl Instant Noodle Line

油炸杯(碗)装方便面生产线





Features 特点

Manufactured with precision using high-quality materials and superior craftsmanship. Key components are made of SUS316 stainless steel, such as the alkaline water equipment, flour mixers, and the steaming machine belts, etc. The pressure rollers are made of SUS403, which has high hardness, wear resistance, and corrosion resistance. The bearing housings are made of aluminum alloy, which offers advantages such as high strength, high modulus of elasticity, good vibration damping, and excellent corrosion resistance. The equipment is equipped with British RITORK pneumatic valves and steam valves that comply with DIN standards. Certified by CE, it ensures the smooth export to European and American countries

采用优质材料和卓越工艺精密制造。关键部件采用 SUS316 不锈钢,例如,碱水设备、和面机和蒸面机网带等。压辊采用 SUS403,具有高的硬度、耐磨性和耐腐蚀性。轴承座采用铝合金,比强度高、弹性模量大、消震性好和耐腐蚀性能好等优点。配置英国 RITORK 气动阀门和符合 DIN 标准的蒸汽阀门。通过 CE 认证,确保机器顺利出口欧美国家。

Specification 规格	FCN-200A	FCN-200B	FCN-300A	FCN-300B	FCN-400A	FCN-400B	FCN-500A	FCN-500B	FCN-600A	FCN-600B	FCN-700	FCN-800	FCN-900	FCN-1000	FCN-1200	FCN-1500
Output (bags/8h) 产量 (杯/8h)	40,000 60,000 70,000 90,000 100,000 120,000 150,000 160,000 180,000 200,000 230,000 260,000 290,000 350,000 440,000															440,000
Rated Power 额定功率(kW)	50-160															
Steam Consumption 蒸汽消耗量(kg/h)		900-4500														
Operator/shift 操作员/班次								5-1	0							
Overall Dimensions 外形尺寸(L*W*H)(M)								(80-120)*	(3-5)*6.5			1		1 /		













HESHAN® 河山机器有限公司 HESHAN MACHINERY CO.,LTD.

Dried Noodle Production Line

烘干面产线





Specification 规格	DN-200A	DN-200B	DN-300A	DN-300B	DN-400A	DN-400B	DN-500A	DN-500B	DN-600A	DN-600B	DN-700	DN-800	DN-900	DN-1000	DN-1200	DN-1500
Output (bags/8h) 产量(袋/8h)	40,000 60,000 70,000 90,000 100,000 120,000 130,000 150,000 160,000 180,000 200,000 230,000 260,000 290,000 350,000 440,000														440,000	
Total Power 总功率(kW)	40-150															
Steam Consumption 蒸汽消耗量(kg/h)		900-4200														
Operator/shift 操作员/班次		5-8														
Overall Dimensions 外形尺寸(L*W*H)(M)		70-110														
Noodle Weight(g/pc) 面条重量(克/件)								7	70						<u> </u>	<u> </u>










HESHAN ® 河山机器有限公司 HESHAN MACHINERY CO.,LTD.

Stick Noodle Production Line 挂面生产线





Features 特点

The stick noodles produced by Heshan production line are carefully dried at a relatively lower temperature compared to other dried noodle products. By hanging the noodles to dry slowly, we preserve their original flavor. Our Stick Noodles Line produces these high-quality noodles through the following series of processes, all meticulously managed by our specialized Stick Noodles Machines.

河山生产线生产的挂面在相对较低的温度下精心烘干,与其他烘干挂面产品相比,这种方式能够更好地保留面条的原始风味。通过缓慢悬挂干燥,我们确保了面条的品质和口感。河山挂面生产线通过以上一系列精细工艺流程生产这些高品质面条,整个过程均由我们专业的挂面生产设备严格把控。

Specification 规格	SN-200	SN-300	SN-400	SN-500	SN-600	SN-700	SN-800
Output 产量(Kg/8h)	2000	3000	4000	5000	6000	7000	8000
Total Power 总功率(kw)	35	40	45	50	55	60	65
Heat Energy Consumption 热能消耗(kcal)	600,00	900,00	1,200,00	1,500,00	1,800,00	2,100,00	2,400,00
Operator/shift 操作员/班次	4	4	5	5	6	6	6
Plant Dim. m² 车间面积	500	600	700	800	900	1000	1100

生产设备





Compound Rolling Machine 复合片机

 Continuous Rolling Machine 连续压片机



Putting-Up Machine 上挂机



◆ Drying Transmission 烘干传输 Trimming Machine 切齐机



 Dynamic Automatic Drying Machine 动态自动烘干机

生产设备




25/26







Yee Mee Crispy Fried Instant Noodle Production Line 伊面生产线



Flow Chart of Raw Fried Yee Mee (Crispy Noodles) Production Line 生炸伊面工艺流程



Specification 规格	RYN2K	RYN3K	RYN5K	RYN8K	RYN12K	RYN15K	CYN2K	CYN3K	CYN5K	CYN8K	CYN12K	CYN15K		
Kinds 类型	Raw Fried Yee Mee Production Line 生炸伊面生产线 Pre Cooked Fried Yee Mee Production Line 預煮													
Capacity(Cake/Hour) 产量(饼/小时)	2,000 3,000 5,000 8,000 12,000 15,000 2,000 3,000 5,000 8,000 12,000 15,000													
Electric Power 电功率(kW)	30-90													
Heat Power 热功率 (Mcal/h)	200-1000													
Type of Heating 加热方式		Natural gas, petroleum gas, Uight oil and electricity,etc 天然气,石油气,轻油,电热等												
Overall Dimensions 外形尺寸 (M)						20-	-60							
Operator/shift 操作人员/班						2-	-3							
Noodle Weight(Grams/Cake) 面条重量						60-	-80							



Dough Mixer Platform 和面机平台







生产设备







Cutting And Shaping Machine 切断整形机

○ Filter System 过滤系统






○ Cooling Machine 冷却机 Cooling Machine 冷却机



 Yee Mee Noodle Frying Machine 伊面油炸机

Wonton Skin & Fresh Noodle Production Line 云吞皮和新鲜面条生产线



>

Features 特点

The Heshan Fresh Noodle Production Line adopts a high degree of automated control. The software is designed by Siemens, and the hardware consists mostly of well-known European and Japanese brands. Through the use of HMI and PLC, the production line achieves synchronized automated operation, which includes advanced software design, a synchronized tracking system, and a photoelectric sensing system. The continuous sheeting machine's pressure rollers are driven by independent motors, which are precisely synchronized through ABB frequency converters and Siemens PLCs, eliminating the need for sheets in both directions, and once initially calibrated, it rarely requires further adjustment. The automated system not only ensures product quality but also saves labor for customers. The entire production line requires only three operators.

河山新鲜面生产线采用高度自动化控制,软件由西门子设计,硬件多为欧日知名品牌。通过 HMI 和 PLC,生产线实现自动化同步运行,包含先进软件设计、同步跟踪系统和光电感应系统。连续压片机的压辊独立电机驱动,通过 ABB 变频器和西门子 PLC 精准同步,无需熟练工人操作。压片机可双向调节面片厚度,首次调试后极少需要再调节。自动化系统不仅保证产品质量,还为客户节省人力,整条生产线仅需 3 名操作人员。

The production capacity can be selected from 200 kg/h to 2000 kg/h.

产量从200KG/H到2000KG/H,可任意选择。

200-2000 KG/H



 Dough Mixing System 真空和面机





 Dough Resting - Feeding - Initial Sheeting Machine 醒面 - 喂料 - 初始压片机



 Dough Sheet Cross-layering Machine 交叉叠皮机





Noodle Rolling Machine 卷面机